

THORSEN TOOLS


Diamalloy Thin Wrenches



One-third thinner—twice as strong. Made of newly developed alloy steel of remarkable strength. Each wrench scleroscope tested. Fit where other wrenches are too large.

No.	Size	Capacity	Thickness	Price
D-74	4"	$\frac{1}{2}$ "	$\frac{5}{16}$ "	\$.90
D-76	6"	$\frac{3}{4}$ "	$\frac{13}{32}$ "	.90
D-78	8"	$\frac{15}{16}$ "	$\frac{15}{32}$ "	1.10
D-710	10"	$1\frac{1}{8}$ "	$\frac{9}{16}$ "	1.40
D-712	12"	$1\frac{5}{16}$ "	$\frac{3}{4}$ "	2.00
D-715	15"	$1\frac{11}{16}$ "	$\frac{31}{32}$ "	3.00
D-718	18"	$2\frac{1}{16}$ "	$1\frac{3}{16}$ "	5.00
D-724	24"	$2\frac{7}{16}$ "	$1\frac{7}{16}$ "	7.50

DIAMOND FULL POLISHED



Buffed to high polish except on knurled nut and inner web of handle.

Number	A44	A46	A48	A410	A412	A415	A418
Size, inches	4	6	8	10	12	15	18
Capacity, in.	$\frac{1}{2}$	$\frac{3}{4}$	$\frac{15}{16}$	$1\frac{1}{8}$	$1\frac{5}{16}$	$1\frac{11}{16}$	$2\frac{1}{16}$
Price each \$	0.65	.65	.80	1.00	1.50	2.25	3.25

Diamond and Diamalloy Parts


Diamond and Diamalloy parts are 100% interchangeable with all standard adjustable Wrenches. In ordering be sure to specify whether Regular or Alloy.



NO. 1. HANDLE NOT SUPPLIED AS REPAIR PART

Size	No. 2 Jaw		No. 3 Knurl		No. 4 Pin	
	Regular	Alloy	Regular	Alloy	Regular	Alloy
4.....	\$.25	\$.25	\$.10	\$.12	\$.05	\$.05
6.....	.25	.25	.10	.12	.05	.05
8.....	.30	.35	.12	.14	.05	.05
10.....	.40	.45	.15	.16	.05	.05
12.....	.60	.70	.25	.26	.10	.10
15.....	.85		.35		.10	
18.....	1.15		.55		.10	

MOTOR SPECIAL COMBINATION PLIERS



A hand-finished tool made from special steel, drop forged, machined and hardened by special methods to meet the needs of the most particular. Bolt and nut turned from solid bar of steel and case hardened. Knurled handles with screw driver except on 5-inch size.

Double

Nickel No.	Size Inches	Capacity Inches	Weight Ounces	Price Each
K15	5	$\frac{3}{4}$	$3\frac{1}{2}$	.45
K16	6	1	8	.50
K18	8	$1\frac{1}{4}$	10	.65
K110	10	$1\frac{1}{2}$	16	.90
N16	6	Thin Straight Nose		.50